# PORTLAND CEMENT (CEM I 52,5N)





# Ordinary Portland Cement (OPC) is a high strength cement suitable for a wide variety of applications.

It is the most commonly used cement in the UK. It can be used on its own or in conjunction with other supplementary materials such as Fly Ash, Limestone and GGBS.

Our cement range is quality-assured with third-party accreditation, and carries the UK CA Mark. We operate in compliance with an accredited ISO management system and all our products conform to BS EN 197-1.

### **FEATURES & BENEFITS**

- High strength performance at all ages
- Versatile for use with a range of admixtures and additions
- It is compatible with an extensive range of additives and admixtures that enhance the characteristics of the end product

# **APPLICATIONS**

- Structural
- Readymix
- Precast
- Screeds
- Mortars
- Render
- Grouts
- Volumetric

# **STORAGE**

Can be stored in a silo ready for use.

# **AVAILABILITY**

Available in bulk loads delivered by tanker. Site must have suitable access for vehicles and a safe discharge point.

# TECHNICAL DATA (TYPICAL PERFORMANCE)

Compressive Strengths (Mpa)	
2-day	32.5
7-day	48.0
28-day	61.0
Setting time (mins)	135
Declared mean Alkali content (%)	0.75
Declared maximum Chloride content (%)	0.09









# PORTLAND CEMENT (CEM I 52,5N)



#### **CONDITIONS OF USE**

- It is essential to use the correct materials, proportion and mix the materials properly, add the correct amount of water, compact, cure and protect as appropriate.
- Holcim cannot be held responsible where workmanship has not been carried out in accordance with good practice.

### **GOOD SITE PRACTICE**

- A risk assessment should be carried out before commencing any work.
- We recommend that trials are undertaken when using a new source of cement. Samples are available on request for trial work and technical support is also available.
- To maintain strength the water/cement ratio should be kept low and admixtures should be used to achieve the required workability.
- The use of cementitious additions e.g. Fly Ash and GGBS will affect overall strength and workability.
- Concrete should be placed by experienced contractors who have the correct training.

#### **SUSTAINABILITY & LOCAL SOURCING**

# Energy use and greenhouse gas emissions

Holcim UK is at the forefront of sustainability and has committed to reducing both energy and greenhouse gas intensity 5% year-on-year.

## **Manufacturing location**

Produced in the UK under strict environmental and social legislation, for local supply.

#### Circular economu

We improve resource efficiency through reuse, recovery and/or recycling of waste materials in our production processes.

Plus, we minimise the generation of both hazardous and non-hazardous waste.

#### **Responsible sourcing**

Holcim UK was the first UK construction company to achieve accreditation to the BES 6001 Framework Standard for the Responsible Sourcing of Construction Products.

# Holcim UK has achieved a 'Very Good' rating for major product groups. The BES 6001 standard assesses:

- Quality Management
- Environmental Management
- Health and Safety Management
- Greenhouse Gas Emissions
- Minimising Raw Material Usage
- Labour Practice
- Biodiversity
- Community Engagement

## **POLICIES**

Holcim policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website **www.holcim.co.uk.** 

#### **COSHH DATA**

Full COSHH data is available on request.

#### **HEALTH & SAFETY**

Contact between cement powder and skin or body fluids (e.g. eye fluids) may cause irritation, dermatitis or burns. Cement is classified as an irritant under the Chemicals (Hazard Information and Packaging) Regulations. Please refer to the product safety data sheet for full information.

## **TECHNICAL SUPPORT**

Should you require information for this or any other product within the Holcim range, please contact our Customer Support team on **01455 288392** or email **uk-cement@holcim.co.uk.** 

For technical support email **cement.technical@holcim.co.uk.** Alternatively, visit our website at: **www.holcim.co.uk.** 

### **Holcim UK Cement**

Cauldon Cement Works, Yelsway Lane, Stoke-On-Trent, Staffordshire, ST10 3EQ Visit: www.holcim.co.uk

The information contained within this publication was accurate at time of production. However, Holcim UK reserves the right to introduce modifications or changes to detail at any time without notice. No charge is levied for this publication or advice therein, and accordingly the company, its employees and authorised agents can accept no liability whatsoever, either indirectly or directly arising from the use of its products.







