



Holcim Postmix is a quality-assured premixed and ready-to-use formulation for fixing all types of fence posts.

GENERAL INFORMATION

Holcim Postmix is composed of a selected blend of cements and aggregates intended for domestic use.

FEATURES & BENEFITS

- ▶ Showerproof and recyclable packaging
- ▶ Simple to use. No mixing required, just add to water
- ▶ Sets in 5-10 minutes and then hardens rapidly

APPLICATIONS

Postmix fixes all types of wood, metal and concrete posts in all types of soil. Postmix should only be used for fixing posts and should not be used for any other purpose.

STORAGE

This product must be stored in unopened bags clear of the ground. All bags must be sheltered from the weather and stored in a frost-free, cool and dry location, avoiding direct contact with the ground. If stored correctly and used within 155 days of the packing date shown on this bag, the activity of the reducing agent* will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble chromium (VI) of the total dry weight of cement. Use of this product after the end of the declared storage period (see above) may increase the risk of an allergic reaction.

AVAILABILITY

Available in 20kg plastic bags.

USAGE GUIDE

1. Dig a hole to the required size for your post.
2. Half fill the hole with water and place the post in the hole.
3. Add Postmix uniformly around the post until it is above the water level.
4. Adjust the post into position and support for approximately 10 minutes until secure.

QUALITY MANAGEMENT

- ▶ Our Postmix is manufactured under a registered ISO 9001 Quality System.
- ▶ Materials used comply with the following standards: Cement BS EN 197-1 & Aggregate BS EN 12620.
- ▶ Admixtures do not contain calcium chlorides.
- ▶ Water added on site should be clean and free from impurities.

TECHNICAL DATA

| Post shape & size | Hole size (width x depth) | Bags required (approx) |
|--------------------|------------------------------|---------------------------|
| Round 2 (50 mm) | 6" (150 mm) x 12" (300 mm) | Bag |
| | 6" (150 mm) x 18" (450 mm) | ½ Bag |
| | 6" (150 mm) x 24" (600 mm) | ¾ Bag |
| | 8" (200 mm) x 12" (300 mm) | Bag |
| | 8" (200 mm) x 18" (450 mm) | 1 Bag |
| | 8" (200 mm) x 24" (600 mm) | 1½ Bags |
| Square 3" (75 mm) | 8" (200 mm) x 18" (450 mm) | ¾ Bag |
| | 8" (200 mm) x 24" (600 mm) | 1 Bag |
| | 8" (200 mm) x 30" (750 mm) | 1½ Bags |
| | 12" (300 mm) x 18" (450 mm) | 2¼ Bags |
| | 12" (300 mm) x 24" (600 mm) | 3 Bags |
| Square 4" (100 mm) | 12" (300 mm) x 30" (750 mm) | 3¾ Bags |
| | 8" (200 mm) x 18" (450 mm) | Bag |
| | 8" (200 mm) x 24" (600 mm) | ¾ Bag |
| | 8" (200 mm) x 30" (750 mm) | 1 Bag |
| | 12" (300 mm) x 18" (450 mm) | 2 Bags |
| | 12" (300 mm) x 24" (600 mm) | 2¾ Bags |
| | 12" (300 mm) x 30" (750 mm) | 3½ Bags |

ADDITIONAL INFORMATION

- Technical data and guidelines based on ambient conditions of +20°C and 50% relative humidity. Lower temperatures may prolong and higher temperatures may shorten indicated values.

SUSTAINABILITY & LOCAL SOURCING

Energy use and greenhouse gas emissions

Holcim UK is at the forefront of sustainability and has committed to reducing both energy and greenhouse gas intensity 5% year-on-year.

Manufacturing location

Produced in the UK under strict environmental and social legislation, for local supply.

Circular economy

We improve resource efficiency through reuse, recovery and/or recycling of waste materials in our production processes. Plus, we minimise the generation of both hazardous and non-hazardous waste.

Responsible sourcing

Holcim UK was the first UK construction company to achieve accreditation to the BES 6001 Framework Standard for the Responsible Sourcing of Construction Products.

Holcim UK has achieved a 'Very Good' rating for major product groups. The BES 6001 standard assesses:

- Quality Management
- Environmental Management
- Health and Safety Management
- Greenhouse Gas Emissions
- Minimising Raw Material Usage
- Labour Practice
- Biodiversity
- Community Engagement

POLICIES

Holcim' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website www.holcim.co.uk.

COSHH DATA

Full COSHH data is available on request.

HEALTH & SAFETY

If this product is used after the end of the declared shelf life the chromium (VI) content may be more than 2ppm. Use of cementitious products containing more than 2ppm chromium (VI) is prohibited, unless in closed, totally automated processes (Control of Substances Hazardous to Health (Amendment) Regulations 2004). Please refer to the product safety data sheet for full information.

TECHNICAL SUPPORT

Should you require information for this or any other product within the Holcim range, please contact our Customer Support team on **01455 288392** or email uk-cement@holcim.co.uk

For technical support email cement.technical@holcim.co.uk
Alternatively, visit our website at: www.holcim.co.uk

Holcim

Cauldon Cement Plant, Earlsway Lane,
Stoke-On-Trent, Staffordshire, ST10 3EQ

Visit: www.holcim.co.uk

The information contained within this publication was accurate at time of production. However, Holcim UK reserves the right to introduce modifications or changes to detail at any time without notice. No charge is levied for this publication or advice therein, and accordingly the company, its employees and authorised agents can accept no liability whatsoever, either indirectly or directly arising from the use of its products.